

SECTION 1 – MANUFACTURER INFORMATION

MANUF/DIST. Majestic Solutions Distributing Co, Inc.
1310 G. Corporation Pkwy
Raleigh, NC 27610
PREPARER/CONTACT: Jeff Todd – For product information, 919-212-1150
MEDICAL/TRANSPORATION EMERGENCY:INFOTRAC 800-535-5053

TRADE NAME/SYMOYMS: SPRAY WAX
CHEMICAL NAME/SYNOMYMS: NOT APPLICABLE
CHEMICAL FAMILY: NOT APPLICABLE
FORMULA: Proprietary
PRODUCT CODE: NOT APPLICABLE

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM:

Health	1				4 = Extreme
Fire	1				3 = High
Reactivity		1			2 = Moderate
Specific	X				1 = Slight
					0 = Insignificant
					X = See Text

SECTION 2 - HAZARDOUS INGREDIENTS

NAMES OF HAZARDOUS INGREDIENTS: See CFR29§1910.1200 (I)-(13) Page 372

CHEMICAL/COMMON NAME	CAS#	PERCENTAGE	PEL-OSHA	TLV-ACGIH
2 Butoxy Ethanol (Skin)	111-76-2	>1	50PPM	25PPM
Light Napthenic Pet. Distilltes	64742-53-6	>1	5mg/m3	5mg/m3
Quarternary Amine	Mixture	>1	N/I	N/I

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA)

SECTION 3 – HEALTH HAZARD DATA

HEALTH EFFECTS (Acute and Chronic):

- *Acute*
- a) Eyes – Vapor, liquids and mists are extremely corrosive to the eyes.
 - b) Skin – Corrosive to skin.
 - c) Inhalation – Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even asphyxiation.
 - d) Ingestion – Can cause gastro-intestinal irritation, nausea, vomiting, and diarrhea.
- *Chronic*
- a) May result in areas of destruction of the skin tissue.
 - b) Overexposure to glycol ethers (in its pure state) has apparently been found to cause anemia, liver abnormalities in laboratory animals.
 - c) May result in areas of destruction of skin tissues or primary irritant dermatitis. Inhalation of dust or mist may cause varying degrees of damage to the affected tissue. May cause skin sensitization – body rash.

PRIMARY ROUTES OF ENTRY: a) Skin b) Inhalation

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to product.

EMERGENCY FIRST AID PROCEDURES:

- A) Skin – Immediately flush skin with lots of running water for at least 30 minutes. Remove contaminated clothing and shoes. Wash before reuse.
- B) Eyes – Flush immediately with large quantities of water for at least 15 minutes. Consult physician.
- C) Inhalation – If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. If breathing is difficult, administer oxygen. Keep person warm, quiet and get medical attention.
- D) Ingestion – Do not induce vomiting. Call physician immediately. If conscious give lots of water or milk. Do not give anything by mouth to an unconscious or convulsing person.

SECTION 4 – CHEMICAL DATA

BOILING POINT (F):	212	SPECIFIC GRAVITY (WATER=1)	0.945
VAPOR PRESSURE (mmHg)	17.00	PERCENT VOLATILE BY VOLUME (%)	>85.00
VAPOR DENSITY (AIR = 1)	0.6	EVAPORATION RATE (WATER = 1)	

SOLUBILITY IN WATER: 100%

APPEARANCE/ODOR: Yellowish liquid with solvent odor.

SECTION 5 – FIRE + PHYSICAL HAZARD DATA

FLASH POINT (Method Used): None FLAMMABLE LIMITS: LEL=N/A UEL=N/A

AUTO-IGNITION: N/A

EXTINGUISHING MEDIA: N/A, Product is not a fire hazard but residue can burn after water evaporates. In case of fire, water spray, carbon dioxide, alcohol type foam applied. Keep containers cool with water spray using fog nozzles.

SPECIAL FIRE FIGHTING PROCEDURES: None

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

INCOMPATIBILITY: (Material To Avoid): Avoid contact with acids and strong oxidizers such as permanganate, chlorine, etc.

HAZARDOUS DECOMPOSITION PRODUCTS: Burning may produce oxides of carbon and traces of hydrocarbons.

HAZARDOUS POLYMERIZATION WILL NOT OCCUR

THIS PRODUCT IS STABLE

SECTION 6 – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Absorb the large spill on suitable absorbable and collect for disposal.

WASTE DISPOSAL METHODS: Dispose of according to local, state and federal regulations for petroleum distillates.

SECTION 7 – EXPOSURE CONTROL INFORMATION

VENTILATION:

LOCAL EXHAUST: Below TLV(s)

MECHANICAL (General): Explosion Proof

SPECIAL: N/A

OTHER: N/A

RESPIRATORY PROTECTION: An appropriate NIOSH approved hydrocarbon canister or respirator for organic vapor should be worn if needed.

PROTECTIVE GLOVES: Wear resistant gloves such as nitrile, rubber, PVC, etc.

OTHER PROTECTIVE EQUIPMENT: To prevent prolonged skin contact, wear impervious clothing and boots.

OTHER ENGINEERING CONTROLS: Eye wash and quick drench facilities.

WORK PRACTICES: Eye wash fountain and safety shower should be easily accessible. Discard properly such items as rags and trash soaked with the product. Provide adequate ventilation.

HYGIENIC PRACTICES: Avoid contact with eyes, skin, and clothing. Avoid inhalation of product vapors. Wash thoroughly after handling and before eating, drinking or smoking. Remove contaminated clothing promptly and wash thoroughly before reused.

SECTION 8 – SPECIAL PRECAUTION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

A) Do not store near acids or acidic materials and oxidizers.

B) Do not store under freezing conditions or above 120 degrees F.

C) Protect from physical damage and keep tightly closed.

MAINTENANCE PRECAUTIONS:

When working with FLAMMABLE material electrically ground all equipment and use only non-sparking tools.

OTHER PRECAUTIONS:

Containers, even those that have been emptied will retain product residue and vapors. Always obey hazard warnings.

Secondary containers and shipping papers should show the following cautions:

KEEP OUT OF REACH OF CHILDREN!